



Format/Program	Skidload	Kem Krest
Bulk	88865794	N/A
Drum	88865798	88865795
Jug	88865799	88865796
Bottle	88865850	88865797

### Product Description:

ACDelco 15W-40 is an advanced, synthetic blend, diesel engine oil that helps extend engine life, allowing you to run your business with confidence. This product meets General Motors requirements and delivers high performance in both on and off-highway applications. Fully backward compatible, ACDelco 15W-40 delivers exceptional performance in both newer and older General Motors heavy duty engine designs. Accordingly, this oil meets or exceeds the requirements of API CK-4, CJ-4, CI-4 PLUS, CI-4 and CH-4 service categories.

ACDelco 15W-40 is a tailored formulation that delivers excellent wear and engine protection, extended drain capability, outstanding high-temperature performance and engine cleanliness.

### Features and Benefits:

ACDelco 15W-40 is formulated with optimized base oil technology, containing severely hydro-processed base stocks and a tailored additive system. This formulation delivers excellent wear protection, outstanding oxidation stability, and outstanding TBN retention. ACDelco 15W-40 also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high-temperature deposits.

### Advantages of ACDelco 15W-40:

- Outstanding oxidation stability
- Extended Oil Drain Interval capability. Reduced low-temperature sludge build-up and high-temperature deposits
- Excellent soot and viscosity control
- Greater engine efficiency, long engine life and long oil life
- Excellent oil consumption control
- Lower oil costs due to less make-up oil during operation
- Outstanding Total Base Number reserves
- Corrosion protection and extended drain intervals for both new and old engines
- Low-temperature fluidity and pumpability
- Formulated for smooth starting in cold weather
- Resistance to corrosive and abrasive wear
- Long life of critical wear surfaces
- Component compatibility - Long gasket and seal life
- Low ash formulation meeting API CK-4 and CJ-4 requirements
- Long emissions after-treatment life (Diesel Particulate Filters, Diesel Oxidation Catalysts, and Selective Catalytic Reduction)



**ACDelco Diesel  
Motor Oil**

**15W-40**



### Specifications and Approvals

ACDelco Diesel Motor Oil meets or exceeds the requirements of:	15W-40
API CH-4	X
API CI-4	X
API CI-4 PLUS	X
API CJ-4	X
API CK-4	X
API SN	X

### Properties and Specifications

Property	15W-40
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	0.9
Density @ 15 C, g/ml, ASTM D1298	0.875
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Hi-Temp Hi-Shear Viscosity @ 150 C $1 \times 10^6 \text{ sec}^{-1}$ , mPa.s, ASTM D4683	4
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	109
Pour Point, °C, ASTM D97	-33
Total Base Number, mgKOH/g, ASTM D2896	9.4

Contact your ACDelco supplier for additional product information. [ACDelcoCanada.com](http://ACDelcoCanada.com)

© 2024 General Motors. All rights reserved. The marks appearing in this ad are the trademarks or service marks of GM, its subsidiaries, affiliates or licensors.

7.14.2023-V2