



ACDelco Synthetic Blend Motor Oil

5W-20
5W-30
10W-30



ACDelco Synthetic Blend 5W-20 (GF-6)

Format/Program	Skidload	Kem Krest
Bulk	19419832	N/A
Drum	19419793	19419790
Jug	19419792	19419789
Bottle	19419791	19419788

ACDelco Synthetic Blend 5W-30 (GF-6)

Format/Program	Skidload	Kem Krest
Bulk	19419831	N/A
Drum	19419784	19419781
Jug	19419783	19419780
Bottle	19419782	19419779

ACDelco Synthetic Blend 10W-30 (GF-6)

Format/Program	Skidload	Kem Krest
Bulk	19420599	N/A
Drum	N/A - Note 1	N/A - Note 1
Jug	N/A - Note 1	N/A - Note 1
Bottle	N/A - Note 1	N/A - Note 1

Note 1 - Replaced by Mobil Special 10W-30

Product Description:

ACDelco Synthetic Blend is formulated from high-quality base oils combined with modern performance additives to help provide long engine life and protect critical engine parts from lubricant related failures for up to 5,000 miles or your vehicle's OEM recommended oil change interval, whichever is longer.

ACDelco Synthetic Blend 5W-20, 5W-30, and 10W-30 contain friction-reducing additives. The American Petroleum Institute (API) classifies these viscosity grades (5W-20, 5W-30, and 10W-30) as "Resource Conserving" engine lubricants, and these viscosity grades meet or exceed ILSAC GF-6 / API SP. Those claims are backward compatible with earlier performance levels such as API SN, SM, SL, and SJ and previous ILSAC categories.

Features and Benefits:

- Helps extend engine life.
- Proven protection of critical engine parts from lubrication related failure for 5,000 miles or your vehicle's OEM recommended oil change interval, whichever is longer.*
- Outstanding wear protection under a wide variety of operating conditions.
- 15% extra cleaning additive to help prevent the formation of sludge and harmful deposits versus Mobil Special oils Enhanced formulation versus Mobil Special oils.
- Meets or exceeds the latest industry specifications (API SP / ILSAC GF-6: ACDelco Synthetic Blend 5W-20, 5W-30 and 10W-30) API SN Plus / Resource Conserving (ACDelco Synthetic Blend 5W-20, 5W-30 and 10W-30)
- Easy cold starting.

*Some limitations apply. For more specific details see the ACDelco Synthetic Blend Motor Oil limited warranty.

Contact your ACDelco supplier for additional product information. ACDelcoCanada.com



ACDelco Synthetic Blend Motor Oil

**5W-20
5W-30
10W-30**



Applications:

ACDelco Synthetic Blend 5W-20, 5W-30, and 10W-30 are recommended for gasoline-fueled automobiles and light-duty trucks requiring an API SN Plus, SN, SM, SL or SJ. They also meet the latest ILSAC GF-6 (Starburst Certification Symbol) specification.

ACDelco Synthetic Blend 10W-40 is recommended for gasoline-fueled automobiles and light-duty trucks where a higher viscosity API SN Plus, SN, SM, SL, or SJ oil is preferred or recommended.

Before using ACDelco Synthetic Blend motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

ACDelco Synthetic Blend meets or exceeds the requirements of:	5W-20	5W-30	10W-30
GM 6094M	X	X	X
API SP	X	X	X
API SJ	X	X	X
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
API SN PLUS	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X	X	X
ILSAC GF-6	X	X	X
Ford WSS-M2C945-A	X		
Ford WSS-M2C945-B1	X		
Ford WSS-M2C946-A		X	
Ford WSS-M2C946-B1		X	
Ford WSS-M2C929-A		X	
Ford WSS-M2C930-A	X		

Properties

Property	5W-20	5W-30	10W-30
Grade	SAE-5W-20	SAE-5W-30	SAE-10W-30
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293			3770
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	5980	6040	
Density @ 15.6 C, g/ml, ASTM D4052	0.8586	0.8581	0.8612
Flash Point, Cleveland Open Cup, °C, ASTM D92	216	220	226
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3	10.3	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	49	63.2	65

Contact your ACDelco supplier for additional product information. ACDelcoCanada.com

© 2024 General Motors. All rights reserved. The marks appearing in this ad are the trademarks or service marks of GM, its subsidiaries, affiliates or licensors.

7.24.2023-V3