



ACDelco dexos[®]1 Full Synthetic Motor Oil

5W-30
0W-20



ACDelco dexos[®]1 Full Synthetic Motor Oil 5W-30

Format/Program	Skidload	Kem Krest
Bulk	19432455	N/A
Drum	19432453	19432452
Jug	19432451	19432449
Bottle	19432447	19432446

ACDelco dexos[®]1 Full Synthetic Motor Oil 0W-20

Format/Program	Skidload	Kem Krest
Bulk	19432465	N/A
Drum	19432463	19432462
Jug	19432460	19432459
Bottle	19432457	19432456

Product Description:

ACDelco Full Synthetic Motor Oil is warranty approved for your General Motors vehicle and meets the demanding dexos[®]1 GEN3 oil specification. ACDelco Full Synthetic Motor Oil can be used in any gasoline fueled General Motors vehicle at the recommended viscosity grade.

ACDelco Full Synthetic Motor Oil 5W-30 is approved against General Motors dexos[®]1 Gen 3 specification.

ACDelco Full Synthetic Motor Oil 0W-20 is approved against General Motors dexos[®]1 Gen 3 specification.

Features and Benefits:

- Helps extend engine life.
- Outstanding wear protection for vehicles of all ages.
- Excellent high-temperature protection to help keep engines cool.
- Permits extended operation at elevated temperatures (up to 400° F) without oxidative oil thickening and oil breakdown.
- Helps control oil consumption and loss.
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts.
- Protection beyond our conventional-synthetic blended products.
- Meets or exceeds the latest industry specifications.



ACDelco dexos[®]1 Full Synthetic Motor Oil

**5W-30
0W-20**



Applications:

ACDelco Full Synthetic Motor Oil can be used in any gasoline-fueled General Motors vehicle at the recommended viscosity grade.

ACDelco Full Synthetic Motor Oil 0W-20 and 5W-30 are recommended for gasoline-fueled automobiles and light-duty trucks requiring an API SP, API SN Plus, SN, SM, SL or SJ. They meet ILSAC GF-6 (Starburst Certification Symbol)

Before using ACDelco Full Synthetic Motor Oil, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product has the following approvals:	0W-20	5W-30
GM dexos1:GEN3 Licensed	X	X
Ford WSS-M2C929-A		X
GM 6094M		X
API SJ	X	X
API SL	X	X
API SM	X	X
API SN	X	X
API SN PLUS	X	X
API SP	X	X
API SN PLUS RESOURCE CONSERVING	X	X
API SN Resource Conserving	X	X
ILSAC GF-6	X	X
Ford WSS-M2C946-B1		X
Ford WSS-M2C947-A	X	
Ford WSS-M2C947-B1	X	

Properties and Specifications

Property	0W-20	5W-30
Grade	SAE 0W-20	SAE 5W-30
Density @ 15 C, g/ml, ASTM D4052	0.845	0.845
Flash Point, Cleveland Open Cup, °C, ASTM D92	231	233
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.2	10.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	43	63
Pour Point, °C, ASTM D97	-39	-45

Contact your ACDelco supplier for additional product information. ACDelcoCanada.com

© 2024 General Motors. All rights reserved. The marks appearing in this ad are the trademarks or service marks of GM, its subsidiaries, affiliates or licensors.

6.28.2023-V2